

Application No. 09/939,412  
Amendment dated November 12, 2004  
Reply to Office Action of August 24, 2004

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

Claim 1 (original): A bone plate assembly, comprising:

a bone plate including first and second extending portions defining an angle therebetween, each of said first and second portions having at least one hole therein; and

a screw extending through a said hole in one of said first and second portions, said screw threadingly engaging another said hole in the other of said first and second portions, wherein said screw spans said angle between said first and second portions.

Claim 2 (original): The bone plate assembly of Claim 1, wherein said first and second portions are placed in slight compression by said threaded engagement between said screw and said hole in said second portion.

Claim 3 (original): The bone plate assembly of Claim 1, wherein said first portion is an elongate plate portion having a plurality of said holes therein, and said second portion is an elongate blade portion.

Claim 4 (previously presented): The bone plate assembly of Claim 3, wherein said screw extends through one of said plurality of holes in said plate portion, and engages said at least one hole in said blade portion, wherein said screw extends through said plate portion to engage said at least one hole in said blade portion.

Application No. 09/939,412  
Amendment dated November 12, 2004  
Reply to Office Action of August 24, 2004

Claim 5 (previously presented): The bone plate assembly of Claim 4, wherein said at least one hole in said blade portion includes a ledge about at least a portion of the periphery thereof, said screw threadingly engaging said ledge.

Claim 6 (previously presented): A bone plate, comprising:

a plate portion and a substantially straight blade portion extending from one another at an angle and connected to one another at a bend, said blade portion including a blade end opposite said angle, said blade end having a blade edge, said bend having a radius defined intermediate said plate portion and said blade portion, said radius dimensioned such that, with said plate portion resting against an outer surface of a bone and said blade portion extending into the bone, said radius fits closely adjacent the outside surface of the bone.

Claim 7 (original): The bone plate of Claim 6, wherein said radius is about 0.25 inches or less.

Claim 8-12 (canceled):

Claim 13 (original): A bone plate assembly, comprising:

a bone plate having elongate plate and blade portions connected to one another at a bend and disposed at an angle with respect to one another, said plate portion having a first hole therein and a second hole therein which is disposed intermediate said first hole and said bend;

a strut screw disposed through said first hole and extending toward said blade portion;

a top screw disposed through said second hole, said top screw extending angularly to one side of said strut screw.

Claim 14 (original): The bone plate assembly of Claim 13, wherein said second hole includes first and second counterbores extending into opposite sides of said plate portion about said

second hole, said first and second counterbores allowing said top screw to be disposed through said second hole in a plurality of different angular positions with respect to said plate portion.

Claim 15 (original): The bone plate assembly of Claim 13, further comprising:  
a third hole disposed intermediate said first and second holes; and  
another top screw disposed through said third hole, said another top screw extending angularly to another side of said strut screw opposite said first side.

Claim 16 (original): The bone plate assembly of Claim 13, wherein said blade portion includes a hole therein through which said strut screw is threadedly engaged.

Claim 17 (withdrawn): A kit, comprising:  
a chisel having an elongate blade portion; and  
a chisel and drill guide member, the chisel and drill guide member having a first channel therethrough, said first channel dimensioned to receive said chisel.

Claim 18 (withdrawn): The kit of Claim 17, wherein said first channel includes a first key element and said chisel includes a second key element, said first and said second key elements engaging one another when said chisel is received within said first channel.

Claim 19 (withdrawn): The kit of Claim 17, wherein said channel and said chisel are cooperatively dimensioned such that said chisel may only be received through said channel according to a single orientation.

Claim 20 (withdrawn): The kit of Claim 17, wherein said chisel and drill guide member further includes a chamfer slot therein, said chamfer slot disposed at an angle relative to said first channel and extending through said chisel and drill guide member to meet said first channel.

Claim 21 (withdrawn): The kit of Claim 17, wherein said chisel and drill guide member further includes at least one second channel therethrough and disposed parallel to said first channel, said kit further including a guide wire disposed through one of said at least one second channels.

Claim 22 (withdrawn): A kit, comprising:

a drill guide insert; and

a chisel and drill guide member, the chisel and drill guide member having a first channel therethrough, said first channel dimensioned to receive said drill guide insert.

Claim 23 (withdrawn): The kit of Claim 22, wherein said first channel includes a first key element and said drill guide insert includes a second key element, said first and said second key elements engaging one another when said drill guide insert is received within said first channel.

Claim 24 (withdrawn): The kit of Claim 22, wherein said channel and said chisel are cooperatively dimensioned such that said chisel may only be received through said channel according to a single orientation.

Claim 25 (withdrawn): The kit of Claim 22, wherein said drill guide insert includes a plurality of guide bores therein.

Claim 26 (withdrawn): The kit of Claim 22, wherein said chisel and drill guide member further includes a chamfer slot therein, said chamfer slot disposed at an angle relative to said first channel and extending through said chisel and drill guide member to meet said first channel.

Claim 27 (withdrawn): The kit of Claim 22, wherein said chisel and drill guide member further includes at least one second channel therethrough and disposed parallel to said first channel, said kit further including a guide wire disposed through one of said at least one second channels.

Claim 28 (withdrawn): A method, comprising:

- providing a chisel and a chisel guide member, the chisel guide member having a channel therethrough dimensioned to receive the chisel, and a chamfer slot extending therethrough to meet the channel, the chamfer slot disposed at an angle with respect to the channel;

- locating the chisel guide member against the surface of a bone;
- inserting the chisel through the channel in the chisel guide member;
- driving the chisel into the bone to form an insertion channel through at least a portion of the bone, the insertion channel defining an opening at the bone surface having a corner portion;

- providing a tool;
- inserting the tool through the chamfer slot of the chisel guide member; and
- removing bone material from the corner portion with the tool to substantially form a chamfer in the edge of the bone at the insertion channel opening.

Claim 29 (withdrawn): The method of Claim 28, further including, before said inserting step, the additional steps of:

- providing a drill guide insert having a plurality of bores therein;
- inserting the drill guide insert within the channel;
- drilling holes into the bone through each of the drill guide holes; and
- removing the drill guide insert from the channel.

Application No. 09/939,412  
Amendment dated November 12, 2004  
Reply to Office Action of August 24, 2004

Claims 30 - 40 (cancelled)

Claim 41 (previously presented): A bone plate, comprising:

a plate portion and a substantially straight blade portion extending from one another at an angle and connected to one another at a bend, said blade portion including insertion means for facilitating insertion of said blade portion into a bone, said bend having a radius defined intermediate said plate portion and said blade portion, said radius dimensioned such that, with said plate portion resting against an outer surface of the bone and said blade portion extending into the bone, said radius fits closely adjacent the outside surface of the bone.

Claim 42 (previously presented): The bone plate of Claim 41, wherein said radius is about 0.25 inches or less.